

Water-based primer for non-porous substrates

Uses

- Priming over Scyon sheeting, wet area timber, galvanised iron, zincalume, stainless steel, copper, brass and most metals
- Priming over non-porous Compressed Fibre Cement (CFC) sheeting. (Refer to Limitations section*)
- Priming over glazed tiles to enable re-tiling without etching or grinding
- Priming over sound, painted/powder coated surfaces
- Priming over dense concrete
- Priming over PVC and other non-PE based rigid plastics

Advantages

- Low VOC
- Suitable as primer over non-porous surfaces for Nitoproof water based membranes
- Non-flammable and free of hazardous odours
- Suitable for internal and external priming applications
- Fast drying
- Excellent water resistance
- Cost effective alternative to grinding and etching surfaces
- Australian made

Description

Nitoprime 115 is a primer specifically designed with adhesion enhancing properties for use onto metallic, smooth, dense, and non porous surfaces.

Nitoprime 115 is a safe alternative to hazardous solvent based primers and etching products, to enable the adhesion of a wide range of water based paints, coatings, membranes and adhesives over non-absorbent surfaces.

Properties

Data quoted is typical for this product, but does not constitute a specification.

Wet Form

Specific gravity of mixed product:	1.3kg/litre
Viscosity:	8000 mPa.s
pH:	8
Colour:	Green
Water soluble:	100% soluble in a wet state
Flammability:	Nil
VOC content:	22g / litre

Application Instructions

Surface preparation

Surfaces must be clean, dust free, sound, stable and free of loose foreign material; existing degraded coatings; laitance; release agents; curing compounds and oil/grease residues.

Wiping down with wet cloth and then allowing the surface to dry will help remove dust from the substrate.

When priming over powder coated metals, light abrasion of the surfaces is recommended (240 grit sandpaper is suitable) followed by wipe clean with Fosroc Solvent 10 prior to primer application.

When priming over PVC and rigid plastics, abrasion of the surfaces is recommended (240 grit sandpaper is suitable) prior to primer application.

Application

Nitoprime 115 should be lightly stirred before using, and can be applied to vertical, horizontal and overhead surfaces using a roller or brush.

Nitoprime 115 can be rendered or tiled over – refer to Nitoprime 120 TDS for render mix ratios. Polymer modified cement based tile adhesive is recommended for direct adhesion.

Drying times

Tack free – 15 minutes (will vary with surface porosity).

Dry film – 30 minutes.

Based on normal ambient conditions of 23°C.

As a minimum, double the drying time of primer if applied @ 10°C – do not apply membrane coatings until primer has completely dried.

Cleaning

Product while in a wet state will clean up with water. Once dried product will need to be removed by Fosroc Solvent 10 or by mechanical means.

Limitations

Not designed for use as a UV exposed or trafficable sealer (as a stand-alone product).

Not to be used for applications in immersed areas (as a stand-alone product).

Not suitable for solvent based finishes. Only use water based systems over Nitoprime 115.

*When applying over CFC, it is advisable to conduct a water droplet test to determine the porosity of the particular grade of CFC which can vary. If the water is absorbed quickly into the CFC then it should be considered “porous” and primed with Nitoprime 120.

Fosroc®

Nitoprime 115

Please Note:

Application of all liquid applied membranes and primers should always refer to the surface temperature conditions before commencing and not just ambient temperatures. (There are limitations to how hot/cold the surface temperature can be, when applying liquid based membrane or primer).

For example: ambient temperatures may be 10°C but the substrate could be 0°C and have frost issues. The same applies with higher temperatures: ambient temperature may be 26°C but have a substrate temperature of 36°C

Supply

Nitoprime 115	4 litre Pail	FC000600-4L
---------------	--------------	-------------

Coverage

Coverage of 10 - 12m²/ litre, this may vary depending on surface profile.

Storage

Nitoprime 115 should be kept in a cool, dry store between 5°C and 30°C in the original, unopened containers.

Important notice

A Safety Data Sheet (SDS) is available from the Fosroc website. Read the SDS and TDS carefully prior to use as application or performance data may change from time to time. In emergency, contact any Poisons Information Centre (phone 13 11 26 within Australia) or a doctor for advice.

Product disclaimer

This Technical Data Sheet (TDS) summarises our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this TDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the manner in which, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. Parchem does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether or not in accordance with any advice, specification, recommendation or information given by it.



constructive solutions

Sold under license from Fosroc International Limited.
Fosroc and the Fosroc logo are trade marks of Fosroc International Limited, used under license.

Parchem Construction Supplies Pty Ltd

1956 Dandenong Rd Clayton VIC 3168

Ph: 1800 812 864

www.fosroc.com.au

ABN 80 069 961 968

Distributed in New Zealand by: Concrete Plus Ltd

150 Hutt Park Road Gracefield Ph: 0800 657 156

www.fosroc.co.nz

NZBN 9429033691282